



# enelion Wallbox DUO POWER



## TECHNICAL SPECIFICATION

## WALLBOX DUO POWER

|                                       |  |
|---------------------------------------|--|
| Cover                                 | resistant to weather conditions; anodized aluminium, powder coating, hardened plexiglass |
| Ingress protection                    | IP 54  |
| Impact protection                     | IK10   |
| Residual current protection*          | RCD B / Enelion RCM B + RCD A  |
| Charging connector                    | AC 2x socket Type 2; EN 62196-1  |
| Energy meter                          | built-in   |
| MID Energy meter*                     | 3-phase  |
| Communication module Bridge OCPP 1.6* | offline / Wi-Fi, Ethernet / LTE (GSM)  |
| User interface                        | LED Light bar; OLED Screen   |
| User authorization*                   | RFID + 2 cards (MIFARE / ISO14443) / FreeCharge  |
| Charging points parameters            | 3-phase electric power   |
| Line-to-line voltage                  | 400V   |
| The frequency of the charging point   | 50 Hz  |
| Charging current/power                | 2x 3x32A / 22kW  |
| Charging voltage                      | 3x 230 V AC  |
| Max. charging current                 | 2x 3x32A   |
| Branding *                            | according to the customer's needs  |
| Operating temperature                 | -25 °C / +55 °C  |
| Storage temperature                   | -40 °C / + 80 °C   |
| Max. above sea level                  | 2 000m   |
| Height (mm)                           | 249  |
| Width (mm)                            | 530  |
| Depth (mm)                            | 156  |
| Weight                                | 3,0kg - 3,5 kg   |

\*Optional equipment